

<b>Immersion Tank</b>	
	<b>IT-900</b>
<b>Chamber Temperature Range</b>	Ambient +9°F (5°C) to 140°F (60°C)
<b>Exterior Dimensions</b>	47" x 79" x 37.3" 1200mm x 2000mm x 950mm
<b>Interior Dimensions</b>	39" x 62" x 23.5" 1000mm x 1600mm x 600mm
<b>Lid Open Dimensions</b>	—————
<b>Shipping Dimensions</b>	92.5" x 51.2" x 53.1" 2350mm x 1300mm x 1350mm
<b>Move-in Dimensions</b>	96.5" x 55.1" x 57.1" 2450mm x 1400mm x 1450mm
<b>Net Weight (Empty)</b>	595 lbs. (270 kg)
<b>Gross Weight (w/ shipping package)</b>	728 lbs (330 kg)
<b>Chamber Volume</b>	237.7 gal (900 L)
<b>Ambient Temperature Requirements</b>	+75°F (+24°C) to +82°F (+28°C)
<b>Ambient Humidity Requirements</b>	max. 85% without condensation
<b>Power</b>	230V - 50-60Hz - 1 phase
<b>FLA (230V)</b>	16A
<b>Water Quality</b>	ASTM D1193 Type IV
<b>Water Supply</b>	7 to 28 psi (0.5 to 2.0 kgf/cm <sup>2</sup> )
<b>Water Connection</b>	1/2" hose barb fitting
<b>Water Usage</b>	1.32 gal per day (5 liters)
<b>Gravity Drains</b>	1/2" hose barb fitting