



<b>SSUMe Series</b>		
	<b>SS600UMe</b>	<b>SS1000UMe</b>
<b>Chamber Temperature Range</b>	Ambient +9°F (+5°C) to 140°F (60°C)	
<b>Exterior Dimensions</b>	74.4" x 45.3" x 57.5" 1890mm x 1150mm x 1460mm	76.4" x 44.1" x 63" 1940mm x 1120mm x 1600mm
<b>Interior Dimensions</b>	32.3" x 25.6" x 30.7" 820mm x 650mm x 780mm	47.2" x 31.9" x 33.5" 1200mm x 810mm x 850mm
<b>Lid Open Dimensions</b>	74.4" x 45.3" x 65" 1890mm x 1150mm x 1640mm	76.4" x 44.1" x 73" 1940mm x 1120mm x 1850mm
<b>Shipping Dimensions</b>	78.7" x 47.2" x 61" 2000mm x 1200mm x 1550mm	80.7" x 51.2" x 68.9" 2050mm x 1300mm x 1750mm
<b>Move-in Dimensions</b>	82.7" x 51.2" x 65" 2100mm x 1300mm x 1650mm	84.6" x 55.1" x 72.8" 2150mm x 1400mm x 1850mm
<b>Net Weight (Empty)</b>	408 lbs (185 kg)	463 lbs (210 kg)
<b>Gross Weight (w/ shipping package)</b>	525 lbs (238 kg)	617 lbs (280 kg)
<b>Chamber Volume</b>	159 gal (600 l)	264 gal (1000 l)
<b>Ambient Temperature Requirements</b>	+75°F (+24°C) to +82°F (+28°C)	
<b>Ambient Humidity Requirements</b>	max. 82% without condensation	
<b>Power</b>	230V - 50-60Hz - 1 phase	
<b>FLA (230V)</b>	16A	
<b>Water Quality</b>	ASTM D1193 Type IV	
<b>Water Supply</b>	7 to 28 psi (0.5 to 2.0 kgf/cm <sup>2</sup> )	
<b>Water Connection</b>	1/2" hose barb fitting	
<b>Water Usage</b>	1.32 gal per day (5 liters)	
<b>Gravity Drains</b>	1/2" hose barb fitting	